



SlipFit® cuff with Velcro® closure for a secure fit

Pull tab

Additional IR-X® guard between thumb and index finger

Durable TP-X® palm with reinforced stitching provides superior wet/dry grip and abrasion resistance

Back-of-hand IR-X® Impact Exoskeleton™ with high-flex design provides ANSI/ISEA 138 Level 1 protection on knuckles and fingers

Reinforced TP-X® thumb saddle, index finger and fingertips

Form-fitting, quality materials

High dexterity





Goatskin leather fourchettes and finger crotches for dexterity and durability

H2X® waterproof liner and C40 Thinsulate™ interior liners keep hands warm and dry

Launderable

# 2023X Rig Lizard Arctic®

## PROTECTION ZONES:

		EN388: 2016	
		ANSI/ISEA CUT	GRAM SCORE
		<b>A3</b>	<b>1040</b>
		<b>4244XP</b>	
		ANSI/ISEA 138	ANSI/ISEA PUNCTURE
		<b>1</b>	<b>5</b>
		EN511: 2006	<b>111</b>

## FEATURES:

The Rig Lizard® Series is purpose-built to provide maximum grip in tough situations – with over five grip options for water, oils, muds, and lubricants. Each glove is also equipped with our highly flexible IR-X® Impact Exoskeleton™, keeping hands protected from smash and pinch injuries. This combination of multiple technologies and features makes the Rig Lizard® the ideal solution for common oil, gas, and mining hazards. With options for cold weather protection, your hands can stay safe and comfortable in any environment.

## ATTRIBUTES:

<b>Style:</b>	Mechanics
<b>Grip:</b>	Wet or dry
<b>Cuff Style:</b>	SlipFit® with Velcro®
<b>Sizes:</b>	7/S through 12/3XL

# HexArmor®

Call 1-877-MY ARMOR or visit [hexarmor.com](http://hexarmor.com)

HexArmor® products are cut and puncture resistant, NOT CUT AND PUNCTURE PROOF. Do not use with moving or serrated blades or tools. User shall be exclusively responsible to assess the suitability of the product as specified for any individual application or use. Protection zones are to be used as a general guide. Actual product protection zones may differ. Product features, design, protection zones subject to change.

Protected by U.S. Patent No. D703,389